



IP20

## REFORM CYLINDER

Reform Cylinder a simplified form as its driver is integrated into a single cylindrical body.

### LIGHTSOURCE OPTIONS

CRI 80 & 90 / 2700K, 3000K, 3500K, 4000K, 5000K

### COLOUR CONSISTENCY

MacAdams 3 SDCM

### LUMEN MAINTENANCE

50 000h (L70 B50)

### LIGHT OUTPUT RATIO

> 91%

### MATERIAL

Powder die-cast aluminium

### INSTALLATION

Available for Nordic Aluminium 1-phase and 3-phase tracks

### COOLING

Passive cooling

Lightsource	Power	Beam angles						Dimming	Colour											
LED-module	Colour temp.	CRI	Luminous flux	Module Wattage	System Wattage	10°	15°	20°	24°	30°	40°	50°	60°	None	1-10V	Push-dim	Dali	Silver	White	Black
Clean White	3 000K	CRI 90	3 100Lm	31W	33W	•		•	•		•		•	•		•	•	•	•	
CLU036-1206	3 000K	CRI 80	4 000Lm	31W	33W	•		•	•		•		•	•		•	•	•	•	
CLU036-1206	3 000K	CRI 90	3 300Lm	31W	33W	•		•	•		•		•	•		•	•	•	•	