PERFORMANCE IN LIGHTING



LYRA 20 LED SR

CODE: 06109390



















Series of street luminaires for outdoor use, comprising:

Pole clamp in die-cast aluminium painted with polyester powder for post top installation \emptyset 60, \emptyset 76 or on arms \emptyset 42 - \emptyset 60 Housing manufactured from technopolymer Diffuser with integrated buvre in UV and heat stabilised transparent technopolymer High-transparency polycabonate lenses for best

light transmission
Anti-aging silicone gasket with high resiliency
Switch splitter that automatically disconnects the
power supply when the cable cover is opened
Aluminium heat dissipation system
Light beam obtained by the combination of
multiple LED modules
Stainless steel external screws
Stainless steel attached clips
Galvanised steel gear tray bracket
The "SECURE LIGHT DISTRIBUTION" system
guarantees uniform light distribution even in case

of LED failures
Compliant with the UNI 10819 Standard and with
the Italian regional laws on light pollution
On request, versions with dimmable ballast are
available

Lampholder: LED
Watt: N.8 LED - 68 W
Colour: GREY RAL 7035
Insulation class: II
KELVIN: 4000
IK: IK08 7J xx5

COSΦ ≥ 0,9Optic: ROAD REFLECTOR

Nominal lumen output: 8320 lm
 Real lumen output: 7012 lm

• Lifetime: 50000 h

L: 70

• Code: 06109390





